



**9kg bags**

COVERAGE:  
**2m<sup>2</sup> at 10mm**  
THICKNESS



**Highly insulating thermal base layer. Measured k-value of 0.127W/mk**



**Fast setting and easy to use. Saving you time on installation.**



**Breathable - water vapour permeable.**



**UKCA and CE marked with A1 fire rating.**

**MADE IN BRITAIN**

**Adaptavate**  
Fabric First Solutions

# breathAplasta thermal

REVISED 01 11 2022

## Insulating plaster for solid walls.

**A quick-setting, multi-coat plaster to thermally insulate solid wall properties, reducing energy bills and problems with mould and condensation.**

**Quick and easy way to improve your U-value**  
Quick setting time allows for faster completion on site. Apply up to 40mm per coat and up to 80mm per day with just 2 hours between coats.

**Highly insulating thermal base layer well suited to all solid masonry walls.**  
Apply directly to any solid masonry external facing wall – brick, block and stone. A 50mm coat will improve the U value of a standard solid wall by around 60%.

**A simple Internal Wall Insulation (IWI) system that breathes with you in your building.**  
A fabric first solution to reducing your energy bills for warmer walls & healthier homes.

For more information and to view or download any of our resources, including Declaration of Performance for relevant certifications, please visit [adaptavate.com](http://adaptavate.com) or scan the QR code.

- Declaration of Performance
- Safety Data Sheet
- Installation Videos
- Case studies
- Technical Data Sheet
- Installation Guides
- FAQs
- System guides



breathAplasta  
thermal | universal | smooth

**Adaptavate Ltd** Unit 7 Vertex Business Park, Bristol, BS16 7LB (UK)  
+44 (0) 1453 827800 [info@adaptavate.com](mailto:info@adaptavate.com) [www.adaptavate.com](http://www.adaptavate.com)

SUMMARY SHEET