SPECIFICATION GUIDE BREATHAPLASTA SMOOTH

PRODUCT	
PRODUCT RANGE	Breathaplasta
PRODUCT NAME	Smooth
CODE	BPS20
CATEGORY	Hydraulic lime
TYPE	Pre-mixed, blended-lime plaster (internal use only).
FUNCTION / DESCRIPTION	Breathable finishing plaster. Provides a super-smooth surface finish to plasterboard or when used to skim over existing plaster.
USES	Use to skim over existing lime-based plaster or as part of a new plaster system in modern and traditional construction. Use on walls and ceilings.
FEATURES	Breathable – vapour permeable Hygroscopic – absorbs and desorbs moisture. Fast setting and drying – sets in approx. 60-90 mins per coat.
	Reduces condensation and balances humidity.
BENEFITS	Naturally resistant to mould growth. Fast and easy application. Attractive natural surface finish that's also durable.
APPLICATION APPLICATION	Fast and easy application.
	Fast and easy application.
APPLICATION	Fast and easy application. Attractive natural surface finish that's also durable. Decant powder slowly into measured water, then mix for 3-mins on
APPLICATION MIXING	Fast and easy application. Attractive natural surface finish that's also durable. Decant powder slowly into measured water, then mix for 3-mins on a low-medium speed with a plasterer's whisk (or similar).
APPLICATION MIXING WATER ADDITION PER BAG	Fast and easy application. Attractive natural surface finish that's also durable. Decant powder slowly into measured water, then mix for 3-mins on a low-medium speed with a plasterer's whisk (or similar). 8-9 litres (approx.) Add water to suit. Avoid making mix too loose.
APPLICATION MIXING WATER ADDITION PER BAG COVERAGE PER BAG	Fast and easy application. Attractive natural surface finish that's also durable. Decant powder slowly into measured water, then mix for 3-mins on a low-medium speed with a plasterer's whisk (or similar). 8-9 litres (approx.) Add water to suit. Avoid making mix too loose. 12 square metres at 3mm thickness (approx.)
APPLICATION MIXING WATER ADDITION PER BAG COVERAGE PER BAG MIN THICKNESS	Fast and easy application. Attractive natural surface finish that's also durable. Decant powder slowly into measured water, then mix for 3-mins on a low-medium speed with a plasterer's whisk (or similar). 8-9 litres (approx.) Add water to suit. Avoid making mix too loose. 12 square metres at 3mm thickness (approx.) 1mm
APPLICATION MIXING WATER ADDITION PER BAG COVERAGE PER BAG MIN THICKNESS MAX THICKNESS	Fast and easy application. Attractive natural surface finish that's also durable. Decant powder slowly into measured water, then mix for 3-mins on a low-medium speed with a plasterer's whisk (or similar). 8-9 litres (approx.) Add water to suit. Avoid making mix too loose. 12 square metres at 3mm thickness (approx.) 1mm 2mm

SPECIFICATION GUIDE BREATHAPLASTA SMOOTH

APPLICATION (CONT.)	
DRYING TIME	1 day per 1mm plaster thickness (approx.)
APPEARANCE	
APPEARANCE AS SUPPLIED	Fine grey powder
APPEARANCE AFTER APPLICATION (DRIED)	Pale stone colour, off white
FINISH	Smooth
DECORATION	
PAINT COMPATIBILITY	Compatible with all common internal decorating paints.
RECOMMENDATION	Breathable paints to maintain vapour openness.
OVERCOATING WITH PLASTER	Can be overcoated with compatible plasters.
SUPPLY	
BAG MATERIAL SPEC	Paper construction, 70 gsm. 2 paper layers, 1 film.
DIMENSIONS PER BAG (FILLED)	450mm x 300mm x 120mm
DIMENSIONS PER PALLET	1200 x 1000mm
FULL PALLET QUANTITY	26-50 bags
HALF PALLET QUANTITY	13-25 bags
QTR PALLET QUANTITY	5-12 bags
MANUFACTURER	
COMPANY	Adaptavate Ltd.
ADDRESS	Unit 7, Vertex Park North, Oakwood Drive, Emersons Green, Bristol, BS16 7LB, United Kingdom.
TEL	+44 (0) 1453 827800
EMAIL	info@adaptavate.com
WEBSITE	www.adaptavate.com

