

SPECIFICATION GUIDE

BREATHAPLASTA SMOOTH

PRODUCT

PRODUCT RANGE Breathaplasta

PRODUCT NAME Smooth

CODE BPS20

CATEGORY Hydraulic lime

TYPE Pre-mixed, blended-lime plaster (internal use only).

FUNCTION / DESCRIPTION Breathable finishing plaster. Provides a super-smooth surface finish to plasterboard or when used to skim over existing plaster.

USES Use to skim over existing lime-based plaster or as part of a new plaster system in modern and traditional construction. Use on walls and ceilings.

FEATURES Breathable – vapour permeable
Hygroscopic – absorbs and desorbs moisture.
Fast setting and drying – sets in approx. 60-90 mins per coat.

BENEFITS Reduces condensation and balances humidity.
Naturally resistant to mould growth.
Fast and easy application.
Attractive natural surface finish that's also durable.

APPLICATION

MIXING Decant powder slowly into measured water, then mix for 3-mins on a low-medium speed with a plasterer's whisk (or similar).

WATER ADDITION PER BAG 8-9 litres (approx.) Add water to suit. Avoid making mix too loose.

COVERAGE PER BAG 12 square metres at 3mm thickness (approx.)

MIN THICKNESS 1mm

MAX THICKNESS 4mm

MAX THICKNESS PER COAT 2mm

SETTING TIME PER COAT 60 - 90 minutes (approx.)

NUMBER OF COATS REQUIRED 2 coats advised for all applications

SPECIFICATION GUIDE

BREATHAPLASTA SMOOTH

APPLICATION (CONT.)

DRYING TIME	1 day per 1mm plaster thickness (approx.)
-------------	---

APPEARANCE

APPEARANCE AS SUPPLIED	Fine grey powder
------------------------	------------------

APPEARANCE AFTER APPLICATION (DRIED)	Pale stone colour, off white
--------------------------------------	------------------------------

FINISH	Smooth
--------	--------

DECORATION

PAINT COMPATIBILITY	Compatible with all common internal decorating paints.
---------------------	--

RECOMMENDATION	Breathable paints to maintain vapour openness.
----------------	--

OVERCOATING WITH PLASTER	Can be overcoated with compatible plasters.
--------------------------	---

SUPPLY

BAG MATERIAL SPEC	Paper construction, 70 gsm. 2 paper layers, 1 film.
-------------------	---

DIMENSIONS PER BAG (FILLED)	450mm x 300mm x 120mm
-----------------------------	-----------------------

DIMENSIONS PER PALLET	1200 x 1000mm
-----------------------	---------------

FULL PALLET QUANTITY	26-50 bags
----------------------	------------

HALF PALLET QUANTITY	13-25 bags
----------------------	------------

QTR PALLET QUANTITY	5-12 bags
---------------------	-----------

MANUFACTURER

COMPANY	Adaptavate Ltd.
---------	-----------------

ADDRESS	Unit 7, Vertex Park North, Oakwood Drive, Emersons Green, Bristol, BS16 7LB, United Kingdom.
---------	--

TEL	+44 (0) 1453 827800
-----	---------------------

EMAIL	info@adaptavate.com
-------	---------------------

WEBSITE	www.adaptavate.com
---------	--------------------